EPSON STYLUS™ PRO 10000/CF

Technical Specifications

Model name
EPSON STYLUS PRO 10000

Part number
C362011

Printing technology
Drop-on-Demand EPSON Micro Piezo™ inkjet technology with EPSON Variable Sized Droplet technology

Print quality
Photo realistic print quality on basis of EPSON PerfectPicture Imaging System with 5 pl Ultra Micro Dot™

Nozzle configuration
1.080 nozzles (180 nozzles per colour)

Print resolution
max. 1.440 x 720 dpi

Printing speed
Up to 16.9 m²/h

Ink system
6-colour system with EPSON Quick Dry™ inks in separate ink cartridges (500 ml/colour)

Media management
2 roll paper holders, autom. paper cutter, manual cut sheet feeder, optional manual paper cutter

Roll media core dimensions
Core diameter: 5.08 cm (2"), optional 7.62 cm (3");
Outside diameter: ≤150 mm; with 2 rolls ≤100 mm

Media
Roll paper:
Media width 210–1.118 mm, media thickness 0.08–0.5 mm;
Cut sheet:
Media size A4/B0+, media width 210–1.118 mm,
Media length 279–1.580 mm, media thickness 0.08–0.5 mm;
Poster board:
Media width 515–1.118 mm, media length 420–728 mm, media thickness up to 1.5 mm

Print margins
Roll paper: 15 mm (top, bottom), 3 mm (sides)/
15 mm (top, sides, bottom)/3 mm (top, sides, bottom)
Cut sheet: 3 mm (top, sides), 15 mm (bottom)

Input buffer
128 MB

Emulation
ESC/P Raster

Interfaces
Standard: parallel Centronics 8-bit interface
(supports IEEE-1284, nibble/ECP mode); USB series B;
Ethernet 10BaseT/100BaseTx Autosensing, Firewire IEEE-1394

Print volume
20.000 pages (DIN B0)

Environmental conditions
Temperature: 10–35 °C; humidity: 20–80% RH (operating)

Electrical specification
Rated voltage/frequency: AC 220–240 V/50–60 Hz;
Power consumption: <131 W (operating), <30 W (stand-by)

Standard printer drivers (OS)
Mac OS ≥7.6.1., MS Windows 95/98/NT4.0/2000/ME

Standard accessories
1 power cord, 2 roll feed spindles (2"),
2 roll paper holders, 1 set of ink cartridges (one each for black, yellow, magenta, cyan, light magenta, light cyan),
1 printer driver, 1 paper tray, 1 user manual,
1 roll paper sample (Presentation Matte Paper, 5 m),
1 assembly tool, 1 spare paper cutter blade

Options

Auto take-up reel unit	C815172
Take-up reel core	C815121
Roll feed spindle (2")	C811133
Roll feed spindle (2") High tension	C811134
Roll feed spindle (3") High tension	C811122
Spare paper cutter blade	C815131
Manual cutter unit	C815182
Spare manual cutter blade	C815192
Type-B (100BaseTx/10BaseT) Multi Protocol Ethernet I/F card	C823633
Type B IEEE-1394 I/F card (Firewire)	C823723

RIP Support
Support of leading vendors

Dimensions/Weight
Dimensions (W x D x H): 1.865 x 1.225 x 710 mm,
Weight: 132 kg (incl. stand)

Warranty
1 year manufacturer's warranty with on-site service,
Optional: 3 year on-site service COVERPLUS

Model name
EPSON STYLUS PRO 10000CF

Article number
C362051

Printing technology
Drop-on-Demand EPSON Micro Piezo™ inkjet technology with EPSON Variable Sized Droplet technology

Print quality
Photo realistic print quality on basis of EPSON PerfectPicture Imaging System with 5 pl Ultra Micro Dot™

Nozzle configuration
1.080 nozzles (180 nozzles per colour)

Print resolution
max. 1.440 x 720 dpi

Printing speed
Up to 16.9 m²/h

Ink system
6-colour system with EPSON ColorFast™ inks in separate ink cartridges (500 ml/colour)

Media management
2 roll paper holders, autom. paper cutter, manual cut sheet feeder, optional manual paper cutter

Roll media core dimensions
Core diameter: 5.08 cm (2"), optional 7.62 cm (3");
Outside diameter: ≤150 mm; with 2 rolls ≤100 mm

Media
Roll paper:
Media width 210–1.118 mm, media thickness 0.08–0.5 mm;
Cut sheet:
Media size A4/B0+, media width 210–1.118 mm,
Media length 279–1.580 mm, media thickness 0.08–0.5 mm;
Poster board:
Media width 515–1.118 mm, media length 420–728 mm, media thickness up to 1.5 mm

Print margins
Roll paper: 15 mm (top, bottom), 3 mm (sides)/
15 mm (top, sides, bottom)/3 mm (top, sides, bottom)
Cut sheet: 3 mm (top, sides), 15 mm (bottom)

Input buffer
128 MB

Emulation
ESC/P Raster

Interfaces
Standard: parallel Centronics 8-bit interface
(supports IEEE-1284, nibble/ECP mode); USB series B;
Ethernet 10BaseT/100BaseTx Autosensing, Firewire IEEE-1394

Print volume
20.000 pages (DIN B0)

Environmental conditions
Temperature: 10–35 °C; humidity: 20–80% RH (operating)

Electrical specifications
Rated voltage/frequency: AC 220–240V / 50–60 Hz;
Power consumption: <131 W (operating), <30 W (stand-by)

Standard printer drivers (OS)
Mac OS ≥7.6.1., MS Windows 95/98/NT4.0/2000/ME

Standard accessories
1 power cord, 2 roll feed spindles (2"),
2 roll paper holders, 1 set of ink cartridges (one each of black, yellow, magenta, cyan, light magenta, light cyan),
1 printer driver, 1 paper tray, 1 user manual,
1 roll paper sample (Doubleweight Matte Paper, 5 m),
1 assembly tool, 1 spare paper cutter blade

Options

Auto take-up reel unit	C815172
Take-up reel core	C815121
Roll feed spindle (2")	C811133
Roll feed spindle (2") High tension	C811134
Roll feed spindle (3") High tension	C811122
Spare paper cutter blade	C815131
Manual cutter unit	C815182
Spare manual cutter blade	C815192
Type B (100BaseTx/10BaseT) Multi Protocol Ethernet I/F card	C823633
Type B IEEE-1394 I/F card (Firewire)	C823723

RIP Support
Support of leading vendors

Dimensions/Weight
Dimensions (W x D x H): 1.865 x 1.225 x 710 mm,
Weight: 132 kg (incl. stand)

Warranty
1 year manufacturer's warranty with on-site service,
Optional: 3 year on-site service COVERPLUS

Your **EPSON** dealer:

www.epson.de

EPSON offers a wide selection of high-quality laser, inkjet, dot matrix, built-in and POS printers, POS systems, mobile computers, scanners, combination devices, digital cameras, data/video projectors, robots and much more.

EPSON COVERPLUS
- **3 year optional extended warranty On-site service option**
- **8 hour response time/next business day**
- **Service hotline**

EPSON COVERPLUS

EPSON is a registered trademark of the SEIKO EPSON CORPORATION.
PostScript is a trademark of Adobe Systems, Inc. LocalTalk is a product of Apple Computer, Inc. TrueType is a trademark of Apple Computer, Inc. LaserJet and PCL are registered trademarks of the Hewlett-Packard company.
Specifications and supply options subject to change. When purchasing, ensure that the original EPSON serial number is on the rear of the device. Printing errors, errors excepted, subject to procedural and program alterations.

ISO 14001 BVQI
Certification number 80679
ISO 9001:2001 BVQI
Certification number 80678

energy
EPA POLLUTION PREVENTER

7000638 – Status 05/02

COLOUR YOUR LIFE

EPSON®

EPSON STYLUS™ PRO 10000/CF

Inkjet printer

The simple solution for maximum outstanding performance:
extremely fast printing, brilliant results,
easy to use, flexible applications